

套筒

增强的，高弹性的，高复原力的
以下各种材质可选：

NR: 天然橡胶，黑色
最大温度. +80 °C

NRL: 天然橡胶，食品级，黑色
最大温度. +70 °C

NRLH: 天然橡胶，食品级，浅色
最大温度. +70 °C

NBR: 丁腈橡胶，食品级，浅色
最大温度. +80 °C

EPDM: 乙丙橡胶，食品质量，黑色
QSV 型最大温度. +80 °C,
其他最大温度. +100 °C

FPM: 氟橡胶，黑色
QSV 型最大温度. +80 °C,
其他最大温度. +100 °C

CR: 氯丁，黑色
最大温度. +80 °C

CSM: 氯磺酰聚乙烯，黑色
最大温度. +80 °C

导电性：
根据要求

Sleeve

Fabric-reinforced, highly flexible, high
reset force, available in the following
qualities:

NR: natural rubber, black,
up to max. +80 °C

NRL: natural rubber, food quality, black,
up to max. +70 °C

NRLH: natural rubber, food quality, pale,
up to max. +70 °C

NBR: nitrile rubber, food quality, pale,
up to max. +80 °C

EPDM: ethylene propylene rubber,
food quality, black,
type QSV up to max. +80 °C,
others up to max. +100 °C

FPM: fluorine rubber, black,
type QSV up to max. +80 °C,
others up to max. +100 °C

CR: chloroprene, black,
up to max. +80 °C

CSM: chlorosulphonyl polyethylene, black,
up to max. +80 °C

Electrical conductive qualities:
upon request



控制 / Triggering

可在单个组件里或者作为一个紧凑单元直接安装在夹管阀上
Available in single components or as a compact unit mounted directly onto the pinch valve.

<p>两位三通电磁阀在无电流时关闭 (常闭型). 3/2-way solenoid valve closed at zero current (NC).</p>	<p>带压力调节器 With pressure regulator.</p>	<p>两位五通电磁阀 5/2-way solenoid valve.</p>	<p>两位三通电磁阀在无电流时开启 (常开型). 3/2-way solenoid valve open at zero current (NO).</p>
<p>带压力开关 With manometric switch.</p>	<p>带单向阀控制锁定，当电流/压力 被切断。 With unblockable non-return valve, cut-off position in case of pressure/ power falling out.</p>	<p>带快速排气阀 With fast vent valve.</p>	<p>在吸入式： 真空泵连接 3 During suction: vacuum pump to connection 3.</p>